

Demand side management in district heating networks

Ralf-Roman Schmidt, Daniele Basciotti,
AIT - Austrian Institute of Technology

5. November 2013

Motivation: peak loads in DH networks



- when a large number of buildings adopt **similar night setback settings**, **large peak loads** can occur thus requiring **peak boiler** to run at expensive **operational costs** and moreover with large **CO₂ emissions**


Literature survey: Night set-back and load shifting

- Significant **energy savings between 15 and 30%** are possible by applying night- and day-time setback strategies e.g. [1-10]
- In different publications the effect of **using the building thermal mass for load shifting** has been assessed and verified e.g. [11-17]
- BUT: none have been researching the potential of peak savings when the measure is **applied at large scale**, e.g. for a city wide DH network

References

- [1] M.M. Manning, M.C. Swinton, F. Szadkowski, J. Gusdorf, K. Ruest, The effect of thermostat set-back and set-up on seasonal energy consumption, surface temperatures and recovery times at the CCHT twin house facility, *ASHRAE Transactions* 113 (1) (2007) 1–12.
- [2] J. Ingersoll, J. Huang, Heating energy use management in residential buildings by temperature control, *Energy and Buildings* 8 (1) (1985) 27–35.
- [3] T. Beckey, L.W. Nelson, Field test of energy savings with thermostat setback, *ASHRAE Journal* 1 (1981) 67–70.
- [4] L.W. Nelson, M.A. Ward, Energy savings through thermostat setback, *ASHRAE Journal* 9 (1978) 49–54.
- [5] L.W. Nelson, J.W. MacArthur, Energy savings through thermostat set-back, *ASHRAE Transactions* 83 (2) (1977) 319–334.
- [6] L.W. Nelson, Reducing fuel consumption with night setback, *ASHRAE Journal* 8 (1973) 41–49.
- [7] Jin Woo Moon, Seung-Hoon Han, Thermostat strategies impact on energy consumption in residential buildings, *Energy and Buildings* 43 (2011) 338–346
- [8] Carlos Haiad, Programmable Thermostats Installed into Residential Buildings: Predicting Energy Saving Using Occupant Behavior & Simulation (2004)
- [9] Szydłowski, et al., Measured Energy Savings from Using Night Temperature Setback (1993)
- [10] J. Kosny et al., Thermal Mass - Energy Savings Potential in Residential Buildings, Buildings Technology Center, ORNL (2001)
- [11] Braun, J. E., Lawrence, T. M., Herrick, R. W., Klaassen, C. J., & House, J. M. (2004). Demonstration of Load Shifting and Peak Load Reduction with Control of Building Thermal Mass. 2004 ACEEE Summer Study on Energy Efficiency in Buildings.
- [12] Wiggels, M., Bohm, B., & Sipilä, K. (2005). Dynamic heat storage optimisation and demand side management. IEA DHC CHP.
- [13] Armstrong, P., Leeb, S., & Norford, L. (2006). Control with Building Mass Part I: Thermal Mass Model. *ASHRAE Transactions Volume 112, Part 1. ASHRAE.*
- [14] Armstrong, P., Leeb, S., & Norford, L. (2006). Control with Building Mass Part II: Simulation. *ASHRAE Transactions Volume 112, Part 1. ASHRAE.*
- [15] Ingvarson, L. O., & Werner, S. (2008). Building mass used as short term heat storage. 11th International symposium on district heating and cooling. Reykjavik.
- [16] Wernstedt, F., & Johansson, C. (2008). Intelligent distributed load control. 11th International symposium on district heating and cooling. Reykjavik, Iceland.
- [17] Karlsson, J. (2012). Possibilities of using thermal mass in buildings to save energy, cut power consumption peaks and increase the thermal comfort. Lund: Lund Institute of Technology.

Load shifting: principle of the optimization algorithm




Case study: DH Altenmarkt (AT)


Region	Tourism region in the Alps (Salzburg)
Network length	ca. 10,3 km main network
Temp. levels	supply: ~95°C, return: ~55°C
customers	204 substations, ~14,6 MW capacity
Heat generation	<ul style="list-style-type: none"> • Biomass boiler 1 (base load 1): 5 MW (used by the DH network: 3,0 - 3,5 MW) • Biomass boiler 2 (base load 2): 2 MW • Fuel oil boiler (peak load): 5,2 MW



Distribution of substation number



Distribution of substation capacities




- EFH
- MFH_gr
- MFH_kl
- Gewerbe + Wohnen
- Fremdenpension
- Hotel
- Bürogebäude
- Groß-Einzelhandel
- Schule
- Gewerbe
- Therme
- Produktionsbetrieb
- Sonstige

Assessment of **load profiles**: building dynamics

- **Side survey** in a demonstration network to determine building properties
 - Age of the Building, Number of (heated) floors, Type of usage, Thermal renovation
- Dynamic **building simulation** to determine the heat up time (Δt)

- Type of walls,
- Air exchange rate,
- Outdoor temperature,
- start temperature,
- Size of the building,
- Heating system




=> **multi parameter variation** in a simplified building model


→ around 95,000 combinations

- Analyses of **building monitoring data** (heat load profiles of every substation, 15 min. resolution) and **calibration of simulations**
-

Assessment of load profiles: principle




monitoring and simulation data **evaluation** (case study)



Application of the load shifting algorithm: **General**


- **Boundary conditions:**
 - day set-point: to be reached between 6 – 8 am
 - start time heating system: as late as possible, 2 am earliest
- **Classification** of the buildings:
 - zone A: $\Delta t < 2$ h, zone B: $\Delta t > 2$ h
- **Parameter variation** for different DH networks
 - random combination of 1000 buildings
 - varying fractions of zone A
- Only ab. 2 % **additional heat load**



Application of the load shifting algorithm: **Conclusions**

- A high number of **buildings with low heat up time** (zone A) is beneficiary for demand side load shifting
 - This is the case for
 - Buildings with a **low thermal mass**
 - Buildings with **oversized substation capacity** (wrong calculation of heat load/ no adaptation of the substation after thermal retrofitting)
- => retrofitted buildings (**without adaptation** of the substation capacity) have a **high flexibility** and are beneficiary for load shifting
- => retrofitted buildings (**with adaptation** of the substation capacity) have a **lower flexibility**, but also contribute less to the overall peak load

Application of the load shifting algorithm: case study



Considerations for **implementation** of load shifting

- **requirements** for the implementation:
 - the **accessibility** of the substation of the building and
 - the **possibility** to remote control
- Two possible **implementation**:
 - at **primary** side level (substation settings such as supply temp. set-point)
 - at **secondary** side level (set-points for heating systems via radiator valves).
- A **first implementation attempt** (using a small number of buildings in the Altenmarkt DH network via remote control of the supply temp.) was largely **unsuccessful** due to a secondary control in the buildings:
 - the room thermostats opened the regulating valves as soon as the secondary supply temperature was reduced.

Conclusions

- a simulation study is presented, exploiting the **implementation of load shifting** in a case study for reducing peak loads due to the night setback.
 - a large database of **validated heating up time for different types of buildings** and outdoor conditions was developed
 - an **optimization algorithm** considering certain flexibility in reaching the day set-point was developed and **applied for a large number of DH networks** with different building structures
 - A high number of buildings with low heat up time is beneficiary => a **reduction of the daily peaks of up to 35% possible** (about 2 % additional heat load)
 - Decreasing the substation capacity reduces the flexibility, but also the individual peak load
 - The **practical implementation** of load shifting measures needs further investigations
-

Thank you for your attention!

Acknowledgment

This presentation is a result of the project “Smart Heat Networks” which is supported with funds from the Climate and Energy Fund and implemented in line with the “New Energies 2020” programme. It is part of the “Smart Grids Modellregion Salzburg”. The authors thank in particular the operator of the district heating network in Altenmarkt (Salzburg AG).






Night setback: Literature survey

source	Type of study	Maximum energy savings [%]
[Manning, 2007]	Experimental	13%
[Ingersoll, 1985]	Analytical investigations	-
[Beckey, 1981]	Experimental	16%
[Nelson, 1973]	Simulation results	15%
[Nelson, 1977]	Simulation results	20%
[Nelson, 1978]	Simulation results	20%
[Woo Moon, 2011]	Simulation results	20%
[Haiad, 2004]	Simulation results	27%
[Szydlowski, 1993]	Experimental	19%
[Kosny, 2001]	Literature review	-

References


- [1] M.M. Manning, M.C. Swinton, F. Szadkowski, J. Gusdorf, K. Ruest, The effect of thermostat set-back and set-up on seasonal energy consumption, surface temperatures and recovery times at the CCHT twin house facility, ASHRAE Transactions 113 (1) (2007) 1–12.
- [2] J. Ingersoll, J. Huang, Heating energy use management in residential buildings by temperature control, Energy and Buildings 8 (1) (1985) 27–35.
- [3] T. Beckey, L.W. Nelson, Field test of energy savings with thermostat setback, ASHRAE Journal 1 (1981) 67–70.
- [4] L.W. Nelson, M.A. Ward, Energy savings through thermostat setback, ASHRAE Journal 9 (1978) 49–54.
- [5] L.W. Nelson, J.W. MacArthur, Energy savings through thermostat set-back, ASHRAE Transactions 83 (2) (1977) 319–334.
- [6] L.W. Nelson, Reducing fuel consumption with night setback, ASHRAE Journal 8 (1973) 41–49.
- [7] Jin Woo Moon, Seung-Hoon Han, Thermostat strategies impact on energy consumption in residential buildings, Energy and Buildings 43 (2011) 338–346
- [8] Carlos Haiad, Programmable Thermostats Installed into Residential Buildings: Predicting Energy Saving Using Occupant Behavior & Simulation (2004)
- [9] Szydlowski, et al., Measured Energy Savings from Using Night Temperature Setback (1993)
- [10] J. Kosny et al., Thermal Mass - Energy Savings Potential in Residential Buildings, Buildings Technology Center, ORNL (2001)

Individual DSM




All customers reach the set point at the same time
 ⇒ **Risk of synchronisation: no reduction of the overall peak load due to individual DSM!**
 ⇒ **Implementation at selected customers could result in a peak loads reduction!**



600 kW (10% of an average consumption peak load)
already shifted → mainly two schools




Fitting of results:

- Visualisation of every heat load profiles per user and simulation results
- Definition of the infiltration rates per user by comparison with monitoring data







Avg. Outside temperature

ΔT night - day set point